

VESTOWAX® SH 105 Pellets**NON-FUNCTIONALISED FISCHER-TROPSCH HARD PARAFFIN****TYPICAL DATA**

Property	Value	Unit	Test method
Drop point	110 – 116	°C	DGF M-III 3
Penetration (needle)	1	mm · 10 ⁻¹	DGF M-III 9b
Viscosity at 120 °C	< 20	mPa s	DIN 52 007/1
Acid number	< 1	mg KOH/g	DGF M-IV 2
Saponification number	< 1	mg KOH/g	DGF M-IV 2
Color	white		
Supply form	pellets		

Disclaimer

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

EVONIK OPERATIONS GMBH

Coating & Adhesive Resins
Paul-Baumann-Str. 1
45764 Marl
Germany

EVONIK CORPORATION

Coating & Adhesive Resins
299 Jefferson Road,
Parsipanny, NJ 07054-0677
USA

**EVONIK SPECIALITY CHEMICALS
(SHANGHAI) CO., LTD.**

55, Chungong Road
Xinzhuang Industry Park
Shanghai, 201108
P.R. China

For contacts in your country, please visit: www.evonik.com/adhesive-resins-contact
E-mail: adhesives@evonik.com
www.evonik.com/designed-polymers